

GF Piping Systems Datasheet

valid from
6/4/09


Ball valves

Ball valve coloro type 355 PVC-U With solvent cement sockets metric



Model:

- Lever blue
- Ball seal HD-PE / lubricant compound
- Monobloc structure
- Actuator unit not connectable
- Only bulk pack GP are delivered



| d [mm] | DN [mm] | PN | EPDM Code | kg | z [mm] | D [mm] | L [mm] | L1 [mm] | L2 [mm] | H [mm] | closest inch | |
|-----------|------------|----|--------------------|-------|-----------|-----------|-----------|------------|------------|-----------|-----------------|--|
| 20 | 15 | 16 | 161 355 002 | 0.130 | 60 | 49 | 92 | 78 | 54 | 51 | 1/2 | |
| 25 | 20 | 16 | 161 355 003 | 0.180 | 66 | 54 | 104 | 92 | 60 | 58 | 3/4 | |
| 32 | 25 | 16 | 161 355 004 | 0.262 | 69 | 64 | 113 | 92 | 63 | 63 | 1 | |
| 40 | 32 | 16 | 161 355 005 | 0.450 | 80 | 78 | 132 | 116 | 74 | 77 | 1 1/4 | |
| 50 | 40 | 16 | 161 355 006 | 0.568 | 85 | 90 | 147 | 116 | 79 | 83 | 1 1/2 | |
| 63 | 50 | 16 | 161 355 007 | 1.027 | 97 | 112 | 175 | 140 | 91 | 102 | 2 | |

The technical data are not binding and not expressly warranted characteristics of the goods. They are subject to change. Our General Conditions of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
 Phone +41 -(0)52-631 1111
 e-mail: info.ps@georgfischer.com
 Internet: <http://www.piping.georgfischer.com>