


GF Piping Systems Datasheet

valid from:
4/4/06

Angle seat check valves

Angle seat check valve type 303 PVC-U With solvent cement spigots metric



Model:

- For horizontal or vertical installation
- Leakproof from: EPDM 2m, FPM 3m water column
- Specific gravity of piston approx. 2 kg/dm³
- Overall length EN 558-1

d [mm]	DN [mm]	PN	kv-value ($\Delta p=1$ bar) [l/min]	EPDM Code	FPM Code	kg	D [mm]	L [mm]	L1 [mm]	L2 [mm]	H [mm]
16	10	10	41	161 303 005	161 303 030	0.094	39	114	120	24	58
20	15	10	95	161 303 006	161 303 031	0.132	43	124	130	28	65
25	20	10	180	161 303 007	161 303 032	0.200	47	144	150	37	75
32	25	10	327	161 303 008	161 303 033	0.323	56	154	160	37	90
40	32	10	484	161 303 009	161 303 034	0.498	64	174	180	44	102
50	40	10	725	161 303 010	161 303 035	0.860	82	194	200	48	123
63	50	10	1130	161 303 011	161 303 036	1.455	95	224	230	60	144
75	65	10	1700	161 303 012	161 303 037	2.499	92	284	290	74	186
90	80	10	2500	161 303 013	161 303 038	3.511	104	300	310	85	204

The technical data are not -binding and not expressly warranted characteristics of the goods. They are subject to change. Our General Conditions of Sale apply.

Georg Fischer Rohrleitungssysteme AG, Postfach, CH-8201 Schaffhausen/Switzerland
Phone +41 -(0)52-631 1111
e-mail: info.ps@georgfischer.com
Internet: <http://www.piping.georgfischer.com>